

# GRANADA

OPTIMAL SOLUTION  
FOR MEDIUM AND  
SMALL POOLS

CLASSIC LINE

YEARS OF WARRANTY | 3 | 2  
TANK EQUIPMENT



High quality  
filtration



- ➔ **Injected filters, unaffected by pool chemicals**
- ➔ **Complete range** with top or side mounted valve
- ➔ **Includes:** 6-way valve, unions and pressure gauge
- ➔ For pools up to 65 m<sup>3</sup>
- ➔ **Wide opening for easy maintenance**



6-way valve



Threaded opening  $\varnothing$  180 mm, to facilitate maintenance operations



Circular base, for perfect stability of the filter

Code	Ref.	Connection	Filtration area (m <sup>2</sup> )	Flow rate (m <sup>3</sup> /h) @ v(m <sup>3</sup> /h/m <sup>2</sup> )		Sand (kg)	Weight (kg)	Vol. (m <sup>3</sup> )
				40	50			
020140142123	GL 400	1,5"	0,13	4,8	6	50	10,5	0,17
020150142123	GL 500	1,5"	0,19	7,6	9,5	100	12,5	0,25
020160142123	GL 600	1,5"	0,28	11,2	14	125	15,5	0,35
020240362123	GT 400	1,5"	0,13	4,8	6	50	10	0,17
020250362123	GT 500	1,5"	0,19	7,6	9,5	100	12	0,25
020260362123	GT 600	1,5"	0,28	11,2	14	125	15	0,35

### Technical Specifications

Operating pressure	0.5 - 1.3 bar
Maximum pressure	2.0 bar
Max. water temp.	50 °C
Connection	1.5"
Tank / Arms / Unions / Cover	PP/PP/ABS/SAN®
Granulometry of filter material	0.4 - 0.8 mm

### Dimensions (mm)

Ref.	A	B	C	D	F
GL 400	266	391	651	503	453
GL 500	345	470	808	503	553
GL 600	391	516	891	503	653
GT 400	720	780	922	503	453
GT 500	877	937	1079	503	553
GT 600	960	1020	1161	503	653

